


Eaton Slip Detection Control
Airflex Product Line



EATON

Powering Business Worldwide

Slip detection control reduces downtime and maintenance costs cause by excessive slip

Eaton, a world leader in clutch-based drive trains for grinding mills, continues to improve drivetrain stability, performance and safety with the release of the Airflex® Slip Detection Control. This easy-to-use solution helps prevent damage to critical, high-value driveline components due to excessive slip.

Slip Detection Control is designed to monitor clutch performance and mitigate the risk of clutch overheating. The control system continuously monitors clutch slip during start up and operation, warning the operator when excessive slip. Excessive slip leads to higher friction wear, overheating of the clutch and increases the risk of fires in the drivetrain.

Features

- Continuously monitors clutch slip during mill operation
- Detects fast and long starts
- Start is aborted if excessive slip time occurs
- Slip is observed when the RPM of the input and output shaft are not equal

Benefits

- Reduces damage to motor, clutch & drive train components
- Increases Uptime
- Reduction in maintenance costs due to reduced friction and overheating of components



Slip detection control: Startup function

Detects fast starts

- A **Fast start** occurs if the grinding mill engages ahead of the preset engagement time
- **System response:** Warning Alert to Operator
- Without monitoring and alert, fast starts may lead to catastrophic drivetrain component damage

Detects long starts

- A **Long start** occurs if the grinding mill start time exceeds the preset engagement time to full RPM
- **System response:** The start is aborted and the clutch instantaneously disengages
- Without monitoring and disengagement, long starts may cause excessive wear, overheating and fires – Damages could exceed \$100k, plus additional fines and downtime

Slip detection control: During operation

Constant and continuous slip monitoring

- Slip detection system continuously monitors the clutch for excessive slip throughout operation – slip differential is a user preset value and can be adjusted for optimization
- **System response:** If excessive slip occurs, the clutch automatically disengages
- Disengaging the drive system when excessive slip occurs during operation prevents excessive friction wear, costly drivetrain component damage, downtime and overheating





Eaton Airflex clutches have the leader in grinding mill clutches for over 30 years. Eaton drives control technology by optimizing grinding mill systems to ensure peak performance.

Eaton
Hydraulics Group USA
14615 Lone Oak Road
Eden Prairie, MN 55344
USA
Tel: 952-937-9800
Fax: 952-294-7722
www.eaton.com/hydraulics

Eaton
Hydraulics Group Europe
Route de la Longeraie 7
1110 Morges
Switzerland
Tel: +41 (0) 21 811 4600
Fax: +41 (0) 21 811 4601

Eaton
Hydraulics Group Asia Pacific
Eaton Building
4th Floor, No.7 Lane280 Linhong Rd.
Changning District
Shanghai 200335
China
Tel: (+86 21) 5200 0099
Fax: (+86 21) 2230 7240

© 2018 Eaton
All Rights Reserved
Printed in USA
Document No.: E-ELCL-BB002-E
January 2018