

TYANA LM Medium duty flat delivery hose



Inner diameter		Working pressure		Burst pressure		Weight	Length
In	mm	bar	psi	bar	psi	g/m	m
1"	25	10	145	29	421	170	50/100
1 1/4	32	9.0	131	27	392	210	50/100
	35	8.0	116	24.0	348	235	50/100
1 1/2	38	8.0	116	24.0	348	250	50/100
	-	40	8	116	24	348	265
-	45	8	116	24	348	290	50/100
2	52	8	116	25	363	320	50/100
	-	60	8	116	24	348	420
2 1/2	64	8	116	24	348	418	50/100
	-	70	8	116	24	348	480
3	76	8	116	23	334	525	50/100
	-	81	7	102	22	319	550
-	90	7.0	102	21	305	660	50/100
4	102	7.0	102	22	319	770	50/100
	-	127	5	73	16	232	1050
6	153	4	58	12	174	1220	50/101
	-	203	3	36	8	109	2100

Construction

- Flexible PVC/NBR lining
- High tensile syntetic textile reinforcement
- Light chemical and weather resistant PVC outer cover

Temperature range

- -10°C to +60°C
- (-14°F to +140°F)

Application

- Medium duty discharge of water, light chemicals and other liquids in construction, agricultrre and industry