

# Eaton Power Xpert™ 9395 UPS

200 - 1100 kVA



## An Eaton Green Solution

Due to outstanding green performance, the 9395 has earned the "An Eaton Green Solution"™ label

### Advanced power protection for:

- Big data centers and server farms
- Financial services
- Building management
- Telecommunications
- Hospitals



Powering Business Worldwide

## Double conversion UPS

### Premium power performance

- Double conversion provides the highest level of protection available by isolating the output power from all input anomalies.
- With a transformer-free design and sophisticated sensing and control circuitry the 9395 UPS delivers an efficiency of up to 94,5%.
- Maximised UPS energy efficiencies with Energy Advantage Architecture (EAA): Variable Module Management System (VMMS) optimises system efficiency at low load levels and Energy Saver System (ESS) allows dramatic increase in UPS efficiency without sacrificing load protection.
- Active power factor correction (PFC) provides 0,99 input power factor and below 3-5% ITHD (depends on utility UTHD), thus eliminating interference with other critical equipment in the same network and enhancing compatibility with generators.
- The UPS is optimised for protecting modern 0,9 p.f. rated IT equipment without the need to oversize.

### True reliability

- Patented Powerware Hot Sync® technology makes possible to parallel up to five UPSs to increase availability or add capacity. The technology enables load sharing without any communication line, thus eliminating single point of failure.
- The multi-module 9395 can be configured with inherent redundancy – anytime the load is below 50%, the system becomes automatically redundant.
- ABM® technology charges batteries only when necessary, preventing batteries corrosion and prolonging batteries service life by up to 50%.

### Extensive configurability

- The 9395 is a completely integrated system that incorporates power modules and system switchgear on factory pre-wired bases.
- A multilingual graphical LCD display makes possible to monitor the UPS status easily.
- Wide software and connectivity options provide monitoring, management and shutdown capabilities over network

### Cost savings and sustainability

- High system efficiency reduces utility cost, extends battery run times and ensures cooler operating conditions.
- Compared to traditional UPS design, a transformer-free UPS is only 50% the weight and occupies just 60% the footprint, thus reducing impact on shipping.
- The new design requires 50-80% less energy in manufacturing due to less energy needed for testing thanks to Easy Capacity Test.
- Pre-wired configuration reduces cabling busbar costs and installation time. Front accessible design minimizes installation costs and saves valuable data centre space.
- A single technical platform used in Eaton's three-phase UPS products guarantees easy upgrades and similarity in service, thus lowering total cost of ownership.
- More than 90% of the materials can be recycled, further decreasing end-of-life impact.

# Eaton Power Xpert™ 9395 UPS 200 - 1100 kVA

## TECHNICAL SPECIFICATIONS

### UPS output power rating

kVA	200	225	275	300	400	450	550	600	675	825	1100
kW	180	202	250	240	360	405	500	480	608	750	1000

### General

Efficiency in double conversion mode (full load)	>94%
Efficiency in double conversion mode (half load)	>93%
VMMS (double conversion)	significantly increased efficiency at low loads

Efficiency in Energy Saver System (ESS)	up to 99%
---	-----------

Distributed parallelling with Hot Sync technology	5 + 1
---	-------

Internal N+1 redundance capable	Yes
---------------------------------	-----

Inverter/rectifier topology	transformer-free IGBT with PWM
-----------------------------	--------------------------------

Audible noise	75 - 81.5 dBA @ 1m, model dependant
---------------	-------------------------------------

Altitude (max)	1000 m without derating (max 2000 m)
----------------	--------------------------------------

### Input

Input wiring	3 ph + N + PE
--------------	---------------

Nominal voltage rating (configurable)	220/380, 230/400, 240/415 V 50/60 Hz
---------------------------------------	--------------------------------------

Input voltage range	+15% / -15%, +10% / -10% for bypass
---------------------	-------------------------------------

Input frequency range	45-65 Hz
-----------------------	----------

Input power factor	0,99
--------------------	------

Input ITHD	< 3-5% on nominal load, depending on the utility UTHD
------------	---

Soft start capability	Yes
-----------------------	-----

Internal backfeed protection	Yes, standard (except on 200/400kVA models)
------------------------------	---

### Output

Output wiring	3 ph + N + PE
---------------	---------------

Nominal voltage rating (configurable)	220/380, 230/400, 240/415 V 50/60 Hz
---------------------------------------	--------------------------------------

Output UTHD	<3% (100% linear load); <5% (reference non linear load)
-------------	---

Output power factor	0.9 (0.8 for 300 & 600 kVA)
---------------------	-----------------------------

Permitted load power factor	0.7 lagging - 0.8 leading
-----------------------------	---------------------------

Overload on inverter	10 min 100-110%; 30 sec 110-125%; 10 sec 125-150%; 300 ms >150%
----------------------	--

Overload when bypass available	Continuous <115%, 20 ms 1000% Note! Bypass fuses may limit the overload capability
--------------------------------	--

### Battery

Type	VRLA, AGM, Gel, Wet Cell
------	--------------------------

Charging method	ABM technology or Float
-----------------	-------------------------

Temperature compensation	with EMP
--------------------------	----------

Battery nominal voltage (lead-acid)	480 V (40 x 12 V, 240 cells)
-------------------------------------	------------------------------

Charging current / Model	200	225	275	300	400	450	550	600	675	825	1100
Default A	40	40	40	38	80	80	80	76	120	120	160

### Dimensions and weights

	W x D x H	Weight
200kVA	1350 x 880 x 1800	810 kg
225,275 and 300kVA	1350 x 880 x 1880	830 kg
400kVA and 200kVA redundant	1890 x 880 x 1880	1390 kg
450/550/600kVA and 225/275/300kVA redundant	1890 x 880 x 1880	1430 kg
450/550 kVA redundant	2520 x 880 x 1880	2030 kg
275 kVA field upgrade UPS-U	740 x 880 x 1880	600 kg
675 & 825 kVA	3710 x 880 x 1880	2730 kg
1100 kVA and 675/825 kVA redundant	4450 x 880 x 1880	3330 kg

### Accessories

External battery cabinets with long-life batteries, X-Slot connectivity (Web/SNMP, ModBus/Jbus, Relay, Hot Sync, ViewUPS-X remote display)

### Communications

X-Slot	4 communication bays
--------	----------------------

Serial ports	1 available
--------------	-------------

Relay inputs/outputs	5/1 programmable
----------------------	------------------

### Compliance with standards

Safety	IEC 62040-1, IEC 60950-1
--------	--------------------------

EMC	IEC 62040-2
-----	-------------

Performance	IEC 62040-3
-------------	-------------