

# SheltR-AIR Outdoor Enclosure



The **Eaton® SheltR Outdoor Enclosure** is designed to provide a secure and clean environment for equipment in harsh or outdoor environments. Typical applications may include communication and telecommunication installations, the housing of data and control equipment, or the support of industrial and process equipment. The SheltR enclosure can accommodate the application equipment, DC or AC backup power, and batteries.

The enclosure is designed to resist harsh environments by employing a combination of extruded aluminium framework, together with powercoated steel panels and aluminium cowlings. The performance is assured by internal insulation to reduce the heating effects from solar gain.

Cooling of the upper equipment compartment is provided by airconditioning (aircon) units to ensure that moisture, pollutants and vermin are kept away from the equipment to be protected, something that cannot generally be achieved by inferior free-air cooled solutions. The electronically controlled aircon fans and compressor are DC powered to ensure that the cooling can be maintained during a power outage\*.

(\* requires a DC backup power solution)

The lower battery compartment shares the same cooling space as the equipment compartment, to ensure batteries are maintained at a reliable temperature.

The air-conditioned version of the SheltR enclosure is intended for hotter climates where active cooling is essential to protect the installed equipment and batteries from high ambient temperatures.

The SheltR enclosure can be preconfigured at the factory with any combination of DC system including: rectifiers, DC distribution, AC distribution, inverters, battery configuration, and control.

For sites that are off grid or connected to an unreliable AC network the enclosure can be preconfigured with a DC system, solar converters, and hybrid control in order to harness energy from sun all-the-while managing the run time of a generator.

Finally remote communications and alarming can be achieved using Eaton's advanced SC300 system controller providing: voltfree contact alarms, Modbus RTU/TCP, SNMP v1/v2/v3, and web access.

## Typical Application

- Solar based installations
- Wireless cell sites & switches
- Transmission terminals
- Data and Control
- Transportation

## Features

- Aluminium frame, roof, and air-conditioning unit cover
- Steel sandwich panel construction
- Attractive powder coat finish
- Polyurethane insulation
- Vandal resistant 3 point locking
- Galvanised steel base
- 48V DC Air-conditioning unit for heat removal
- Accommodates up to 400-450Ah (48V) of battery



Powering Business Worldwide

# Technical Specifications

## Environment: Compartment

Protection	IP55
Cooling	DC powered air-conditioner
Cooling Capacity	CE: 500Watt, 1500Watt (pending) Non-CE: 1000, 2000, 3000Watt  $T_{Ambient} = 35^{\circ}C$ , $T_{Internal} = 35^{\circ}C$
Operating temperature	-15°C to +55°C
Cooling Fans	48V speed controlled (1x external, 1x internal)
Refrigerant	R134a
Noise Level	60-65dB(A)

## Input - Aircon

DC Supply	44 to 58VDC, 48VDC nominal
DC Current	500Watt (3.34Amp), 1500Watt (9Amps), 1000Watt (6.90Amp), 2000Watt (12.0Amps), 3000Watt (18Amps), 48VDC

## Security

Locking	3 point lock mechanism, key locked handle with security panel and padlock clasp.
Hinges	Concealed
Cable Glands	12 cables glands accepting cables of 15mm, as standard

## Equipment Space

Power Compartment	21U, 19" (450mm), 548mm
Battery Compartment H,W,D	340mm, 745mm, 620mm, per shelf. Two shelves.
Batteries	Space for 48V, 400-450Ah (2 shelves, 6 x 12V 100-150Ah front terminal blocks)

In the interests of continual product improvement all specifications are subject to change without notice.

Email: [dc.info@eaton.com](mailto:dc.info@eaton.com)  
[www.eaton.com/dcpowersolutions](http://www.eaton.com/dcpowersolutions)

## Mechanical

Dimensions H,W,D	2100mm, 905mm, 1040mm
Weight	225kg (excluding DC power and batteries or customer equipment)
Finish	Powder coating
Base	Hot dipped galvanised (200mm height)

## Part Numbers

SheltR-AIR-A05CE	SheltR-AIR enclosure with Air-conditioning-based cooling (500Watt) for power and battery compartment. CE compliant DC-powered aircon unit. Not included: DC power, batteries, AC and DC distribution, or cabling.
SheltR-AIR-A15CE	As per SheltR-AIR-A05CE, but with 1500Watt CE compliant air-conditioning-based cooling
SheltR-AIR-A10	SheltR-AIR enclosure with Air-conditioning-based cooling (1000Watt) for power and battery compartment. DC-powered aircon unit. Not included: DC power, batteries, AC and DC distribution, or cabling.
SheltR-AIR-A20	As per SheltR-AIR-A10, but with 2000Watt Air-conditioning-based cooling.
SheltR-AIR-A30	As per SheltR-AIR-A10, but with 3000Watt Air-conditioning-based cooling

## Options

Smoke Detector	Optical smoke detector
Door Switch	Switch for door alarm

## Certifications

Europe	CE
--------	----

**Eaton**  
EMEA Headquarters  
Route de la Longeraie 7  
1110 Morges, Switzerland  
Eaton.com

© 2022 Eaton  
All Rights Reserved  
Publication No. PS154055EN  
April 2022

**EATON**  
Powering Business Worldwide

Eaton, CellSure, SiteSure, DCTools and PowerManager are trade names, trademarks, and/or service marks of Eaton Corporation or its subsidiaries and affiliates. All other trademarks are property of their respective owners.

Eaton is a registered trademark.  
All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

