	8	7	6
Т			
G			
F		(€ €	
E		C C 	
D			
С	PC302-I-MTR REMOTE EPO		

FUNCTIONALITY	INPUT		OUTPUT
POWER CONTROLLER WITH STANDARD REMOTE	5-PT TERMINAL BLOCK		(12) IEC C13, SWI (2) IEC C13, UNS\
MECHANICAL	INPUT RATING		OUTPUT RATING
19.00" (482.6mm) WIDTH 3.44" (87.4mm) HEIGHT 12.00 (304.8mm) DEPTH BLACK CHASSIS	120/208V ~ OR 230/400 3P + N + PE 16A 50/60HZ	v	120V ~ OR 230V ~ 16A MAX PER SECT 16A MAX PER PHAS
CIRCUIT BREAKERS	FILTER AND SPIKE/SURGE		INDICATOR LIGHTS
MAIN: 20A 3-POLE UL RECOGNIZED	EMI/RFI FILTER COMMO AND DIFFERENTIAL MO		ONE GREEN FOR M ONE GREEN FOR EA ON WHEN SECTIO
0	7		C

8

В

А

		ENVIRONMENTAL	
3, SWITCHED		32° TO 113° F	
3, UNSWITCHED		0° TO 45° C	
TING		CERTIFICATIONS	
230V ~ , ER SECTIO ER PHASE	ON		
LIGHTS		ACCESSORIES INCLUDED	
I FOR MAIN POWER; I FOR EACH SECTION, N SECTION IS POWERED		SUB-HRDWARE-001 - PANEL MOUNT KIT SCREWS SPK030 - PANEL MOUNT KIT CAGE NUTS REMOTE02 - REMOTE CONNECTOR KIT (4)	
	5	4	







