



**FRONT VIEW**  
(DOORS AND COVERS REMOVED)

**SIDE VIEW**  
(DOORS AND COVERS REMOVED)

**PLAN VIEW**

**NOTES:**

1. OPERATOR INTERFACE PANEL.
2. SCR MODULE.
3. MAIN INPUT CIRCUIT BREAKER.
4. (4) SUB-FEEDS CIRCUIT BREAKER.
5. MOLDED CASE INPUT SWITCH.
6. MOLDED CASE BYPASS SWITCH
7. MOLDED CASE ISOLATION SWITCH
8. INPUT CABLE AREA TO BE PUNCHED
9. OUTPUT CABLE AREA TO BE PUNCHED
10. RECOMMENDED MINIMUM CLEARANCE:  
FRONT,36" ; REAR,36" ; SIDE,6" ; TOP,12"

UNLESS OTHERWISE SPECIFIED:  
DIMENSIONS ARE IN INCHES  
[ ] IN MILLIMETER  
ANGULAR:  $\pm 0.5^\circ$  BEND  $\pm 1^\circ$   
TWO PLACE DECIMAL  $\pm 0.02$   
THREE PLACE DECIMAL  $\pm 0.005$

THIS DRAWING CONTAINS  
CONFIDENTIAL & PROPRIETARY  
INFORMATION AND SHALL NOT  
BE DISCLOSED OR COPIED  
WITHOUT THE EXPRESSED,  
WRITTEN PERMISSION OF  
SMITHS POWER



		DO NOT SCALE DRAWING	
APPROVALS		DATE	
DRAWN	MJP	1/27/17	
CHECKED	RAE	1/27/17	
ENG. APPR.			

TITLE: STATIC SWITCH PRIMARY SYSTEM 75kVA, (4) SUBFEED		
SIZE <b>B</b>	DWG. NO. <b>SSP56580</b>	REV <b>A</b>
PART NO.		SHEET 1 OF 1