



## NOTES:

- 1. HINGED REMOVABLE PANELS PROVIDED ON SIDES.
- ACCESS: MINIMUM 36" FROM FRONT & REAR OF ENCLOSURE, IS REQUIRED FOR OPERATION. SIDE ACCESS IS REQUIRED FOR INSTALLATION & MAINTENANCE.
- 3. APPROXIMATE WEIGHT: 600lbs.
- 4. (2) CIRCUIT BREAKERS, (2) 42 CIRCUIT PANELBOARD (2) METERS, (2) INPUT BUSES
- 5. (168)- 0.875ø KNOCKOUTS PROVIDED.

THIS DRAWING CONTAINS
CONFIDENTIAL & PROPRIETARY
INFORMATION AND SHALL NOT
BE DISCLOSED OR COPIED
WITHOUT THE EXPRESSED,
WRITTEN PERMISSION OF
POWER DISTRIBUTION INC.

TITLE -OUTLINEREMOTE POWER PANEL (RPP)
(2) MAINS & (2) PANELBOARDS (2) METER (2) INPUT BUS

DWG. NUMBER SHEET 2 OF 2 REVISION

 RPP18278
 -B 

 DRAWN BY ISF
 CHECKED BY LJN

 DATE 04-21-15
 DATE 04-21-15

PDI creating the perfect wave