5" SQUARE LOW VOLTAGE OUTLET BOXES – 67.0 CUBIC INCH CAPACITY UL LISTED

Applications:

- The data communications boxes are ideal for applications requiring the increased capacity including the installation of data communication, fire alarms and other applications requiring larger cubic capacity and knockouts.
- Suitable for healthcare, education, commercial and government facilities
- Ideal for audio, video, data and power applications
- For use with Rigid/IMC and EMT conduit

Certifications and compliances:

• UL Listed

Standard materials and finishes:

- Material steel (.0625 (G60) galvanized)
- Finish natural, blue or red painted



TP5SQ50100

D	D	Brkt.	Descrip.	Grounding method	Cap. cu. in.	Knockouts	
size	depth					Sides	Bottom
boxes	"						
5" sq.	27/8"	-	Welded	-	67.0	12 - ½"+ ¾" C	3 - 1/2", 2 - 3/4"
5" sq.	27/8"	-	Welded	-	67.0	4 - 1/2", 8 - 1"	3 - 1/2", 2 - 3/4"
5" sq.	27/8"	-	Welded	-	67.0	4 - 1", 4 - 11/4"	3 - 1/2", 2 - 3/4"
s boxes							
5" sq.	27/8"	-	Welded	-	67.0	12 - ½"+ ¾" C	3 - 1/2", 2 - 3/4"
5" sq.	27/8"	-	Welded	-	67.0	4 - 1/2", 8 - 1"	3 - 1/2", 2 - 3/4"
5" sq.	27/8"	-	Welded	-	67.0	4 - 1", 4 - 11/4"	3 - 1/2", 2 - 3/4"
s							'
5" sq.	27/8"	-	Welded	-	67.0	12 - ½"+ ¾" C	3 - 1/2", 2 - 3/4"
5" sq.	27/8"	-	Welded	-	67.0	4 - 1/2", 8 - 1"	3 - 1/2", 2 - 3/4"
5" sq.	27/8"	-	Welded	-	67.0	4 - 1", 4 - 11/4"	3 - 1/2", 2 - 3/4"
	5" sq. 5" sq. 5" sq. 5" sq. as boxes 5" sq. 5" sq. 5" sq. 5" sq. 5" sq. 5" sq.	Size depth	size depth Brkt. boxes 5" sq. 2"/8" - - 5" sq. 2"/8" - - - 5" sq. 2"/8" - - - sboxes - - - 5" sq. 2"/8" - - - 5" sq. 2"/8" - - - s - - 5" sq. 2"/8" - - -	Size depth Brkt. Descrip.	Size depth Brkt. Descrip. method	size depth Brkt. Descrip. method cu. in. boxes 5" sq. 2½" - Welded - 67.0 - 67.0 5" sq. 2½" - Welded - 67.0 - 67.0 5" sq. 2½" - Welded - 67.0 - 67.0 as boxes - 67.0 5" sq. 2½" - Welded - 67.0 - 67.0 5" sq. 2½" - Welded - 67.0 - 67.0 5" sq. 2½" - Welded - 67.0 - 67.0 5" sq. 2½" - Welded - 67.0 - 67.0 5" sq. 2½" - Welded - 67.0 - 67.0	Box size Box depth Brkt. Descrip. Grounding method Cap. Cu. in. Sides boxes 5" sq. 2'/s" - Welded - 67.0 12 - ½" + ¾" C - 5" sq. 2½" + ¾" C - 67.0 4 - ½", 8 - 1" - 5" sq. 2½" + ¾" C - 67.0 4 - ½" + ¾" C - 12 - ½" + ¾" C - 5" sq. 2½" + ¾" C - 67.0 12 - ½" + ¾" C - 5" sq. 2½" + ¾" C - 67.0 4 - ½", 8 - 1" - 4 - ½", 4 - ½", 8 - 1" - 8 - 67.0 4 - ½", 4 - ½", 8 - 1" - 8 - 67.0 12 - ½" + ¾" C - 67.0 4 - ½", 4 - ½", 8 - 1" - 8 - 67.0 4 - ½", 4 - ½", 6 - ½", 8 - 1" - 8 - 67.0 12 - ½" + ¾" C - 67.0 4 - ½", 8 - 1" - 8 - - 67.0 4 - ½", 8 - 1" - 4 - 67.0 4 - ½", 8 - 1" - 4 -

5" SQUARE COVERS AND ADAPTERS

UL LISTED



TP5BC



TP5CP

Cat. #	D	Box depth	Brkt.	Descrip.	Grounding method	Cap. cu. in.	Knockouts			
	Box size						Sides	Bottom		
Standard unpainted boxes										
ТР5ВС Э	5" sq.	Blank	-	Cover	-	-	-	-		
TP5CP G	5" sq.		-	4" Sq. adapter	-	-	-	-		
Blue communicati	ons boxes									
TP5BC-BLUE G	5" sq.	Blank	-	Cover	-	-	-	-		
TP5CP-BLUE@	5" sq.	-	-	4" Sq. adapter	-	-	-	-		
Red fire signal box	ces									
TP5BC-RED G	5" sq.	Blank	-	Cover	-	-	-	-		
TP5CP-RED G	5" sq.	-	-	4" Sq. adapter	-	-	-	-		



