

TB300-03SP high SCCR double row terminal block





Catalog number:

• TB300-03SP

Description:

Eaton's Bussmann series catalog number TB300-03SP is a three-pole double row terminal block featuring a high Short-Circuit Current Rating (SCCR) when protected by specific, tested upstream overcurrent protective devices (see SCCR data table for details).

Specifications:

Ratings

- · Volts: 600 Vac/dc
- Amps: 30 A
- SCCR:
 - 10 kA default
 - 100 kA (see SCCR data on page 2)

Agency information

- UL 1059 Recognized, Guide XCFR2, File E62622
- General Industry Class per UL 1059, usage Category C
- RoHS compliant




Mechanical


- Panel mount 3-pole configuration
- 0.562" (14.28mm) pole-to-pole spacing
- Flammability: UL 94 V0

Conductors

- · Cu only, 10 to 18 AWG
- Torque, 15 lb-in

Dimensions - in





Short-Circuit Current Rating data

The high SCCR of this block relies upon the tested, upstream overcurrent protective devices listed in this table

| | | | | | Max. Fuse Class and Amp* | | | | | |
|-------------|------|-----------------------------------|----|-------------------------|--------------------------|-------------|----|---|-----|--------------------------|
| Catalog no. | Amps | Cu wire range line and load (AWG) | | (1) Cu wire range (AWG) | LPJ | JJN, JJS | | | | Min. enclosure size (in) |
| TB300-03SP | 30 | 10 to 18 Cu | 15 | 10 to 18 | 60 | 60 | 30 | _ | 100 | 8 x 8 x 4 |

^{*} Class G 60A (SC-60) or less or Class CC 30A (LP-CC-30, FNQ-R-30, KTK-R-30) or less are suitable for the SCCR in this table.

The only controlled copy of this data sheet is the electronic read-only version located on the Eaton network drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

Eaton

1000 Eaton Boulevard Cleveland, OH 44122 Eaton.com

Bussmann Division 114 Old State Road Ellisville, MO 63021 United States Eaton.com/bussmannseries

© 2016 Eaton All Rights Reserved Printed in USA Publication No. 1061 — BU-MC16126 October 2016 For Eaton's Bussmann series product information, call 1-855-287-7626 or visit: Eaton.com/bussmannseries

