DNV-GL

Certificate No: **E-14282**

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Circuit Breaker

with type designation(s) LW, HLW & LW (800A)

Issued to

Eaton Electrical

Moon Township, United States

is found to comply with

Det Norske Veritas' Rules for Classification of Ships, High Speed & Light Craft and Det Norske Veritas' Offshore Standards

Application:

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.

Rated Voltage (V) 690 Rated Current (A) 315 - 800 Frequency (Hz) 50 - 60

This Certificate is valid until 2019-06-30. Issued at Høvik on 2015-09-29

DNV GL local station: New York

Approval Engineer: Nicolay Horn



for DNV GL

Digitally Signed By: Laumann, Marit Location: DNV GL Høvik, Norway Signing Date: 2015-11-13

Marit Laumann Head of Section

Form code: TA 1411a Revision: 2015-05

© DNV GL 2014. DNV GL and the Horizon Graphic are trademarks of DNV GL AS.

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

Job Id: 262.1-017170-1

Certificate No: E-14282

Name and place of manufacturer

Eaton, One Tuscarawas Road, Beaver, USA

Product description

Technical info:

Product:	Moulded case circuit breakers	
Types:	LW, HLW and LW (800A)	
Number of poles:	3 and 4	
Rated current (A):	315, 400, 630 and 800	
Rated operational voltage :	240, 415 and 690 V AC	
Rated insulation voltage:	690 V	
Rated impulse withstand voltage Uimp:	8 kV	
Rated frequency Hz:	50 - 60	
Utilization category:	A A	
Max ambient temperature:	50 °C	

Short circuit data:

	LW	HLW	LW (800A)
Rated Sho	rt-circult Serv	ice Breaking ca	p. Ics (kA)
240V AC	85	100	33
415V AC	50	70	25
690V AC	10	13	10
Rated Ultim	nate short- cire	cuit Breaking c	ap. Icu (kA)
240V AC	85	100	65
415V AC	50	70	50
690V AC	20	25	20

Application/Limitation

Suitable for use in an IT system with a capacity of 1.2 times the maximum trip current at 690 V AC.

Type Approval documentation

Technical:

"Specification of the Certified Product, Annex to KEMA- KEUR CERTIFICATE no. 2012668.04 issued 2001-06-20. & 2084525.01 issued 2005-06-02.

Test reports:

KEMA test certificate nos.: 2095729.01 & 2095729.02 issued 2008-01-17. KEMA test reports nos.: 2024331.63, 64 & 65 issued 2003-07-25.

CLARK test report no.: EL8006 dated February 2006.
UL EMC test report no.: MC8387 dated 2004-06-06
Alion EMC test report no.: 03_0903_1 dated 2003-07-29.
LF Research test report no.: 2006-152 dated December 2006.

Tests carried out

Type tests according to IEC 60947-2 including EMC, vibration test and damp heat test.

Form code: TA 1411a Revision: 2015-05 www.dnvgl.com Page 2 of 3

Job Id:

262.1-017170-1

Certificate No: E-14282

Marking of product

EATON/Cutler Hammer -HLW/LW- Circuit-Breaker -Type data

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the type approval is complied with and that no alterations are made to the product design or choice of materials.

The main elements of the survey to be dealt with:

- · Ensure that type approved documentation is available.
- Ensure that materials used comply with type approved documents and/or referenced material specifications.
- Review design, materials, performance and production process with respect to possible changes, in order to ensure compliance with the type approved documentation and/or referenced material specifications.
- Ensure traceability between manufacturer's product marking and the DNV Type Approval Certificate.

Assessment to be carried out at least every second year.

END OF CERTIFICATE

Form code: TA 1411a Revision: 2015-05 www.dnvgl.com Page 3 of 3