

MFBA3V1608

Automotive high impedance multilayer chip ferrite bead



Product features

- AEC-Q200
- 0603 (1608 metric) surface mount package
- Impedance range 10 ohms to 2000 ohms
- Multilayer monolithic construction yields high reliability
- Moisture sensitivity level (MSL): 1

Applications

- Body electronics (keyless entry, ECU, antennas)
- Advanced driver assistance systems (ADAS)
- Infotainment and cluster electronics
- Safety electronics systems
- WLAN, WiFi, Bluetooth
- Portable medical devices
- Inventory management equipment
- Displays/monitors
- IoT, remote monitoring
- Testing equipment
- Automation equipment
- Sensors

Environmental compliance and general specifications

- Operating temperature range: -55 °C to +150 °C (ambient plus self-temperature rise)
- Storage temperature (component): -55 °C to +150 °C
- Solder reflow temperature: J-STD-020 (latest revision) compliant



Product specifications

Part number ²	Impedance (Ω) 100 MHz, $\pm 25\%$, @ +25°C	DCR (Ω) maximum @ +25°C	Rated current ¹ (mA) maximum
MFBA3V1608C-100-R	10	0.2	700
MFBA3V1608C-300-R	30	0.25	600
MFBA3V1608C-600-R	60	0.3	600
MFBA3V1608C-121-R	120	0.4	300
MFBA3V1608C-221-R	220	0.6	250
MFBA3V1608K-300-R	30	0.2	700
MFBA3V1608K-600-R	60	0.2	700
MFBA3V1608K-121-R	120	0.25	600
MFBA3V1608K-151-R	150	0.25	600
MFBA3V1608K-221-R	220	0.3	550
MFBA3V1608K-301-R	300	0.35	500
MFBA3V1608K-471-R	470	0.4	350
MFBA3V1608K-601-R	600	0.5	350
MFBA3V1608K-102-R	1000	0.7	200
MFBA3V1608H-152-R	1500	1	200
MFBA3V1608H-202-R	2000	1.2	150

1. Rated current: DC current for an approximate temperature rise of 40 °C without core loss.

2. Part number definition: MFBA3V1608y-xxx-R

MFBA3V1608y = Product code and size (y=Internal code)


xxx = Impedance value in Ω , last character equals number of zeros

-R suffix = RoHS compliant

Mechanical parameters (mm)

Recommended pad layout

Schematic



Part number	A	B	C	D	E	F	G
MFBA3V1608y-xxx-R	1.60 ± 0.15	0.80 ± 0.15	0.80 ± 0.15	0.30 ± 0.20	0.80	0.85	0.95

Part marking: No marking

All soldering surfaces to be coplanar within 0.1 millimeters

Tolerances are ± 0.1 millimeters unless stated otherwise


Pad layout dimensions are reference only

Traces or vias underneath the inductor is not recommended


Packaging information (mm)

Drawing not to scale

Supplied in tape and reel packaging, 4000 parts per 7" diameter reel (EIA-481 compliant)




Bo	1.80 ± 0.05
Ao	0.96 + 0.05/-0.03
Ko	0.95 ± 0.05
P	4.0 ± 0.1
t	0.95 ± 0.05









Type	7" * 8
A	9.0 ± 0.5
B	60 ± 2
C	13.5 ± 0.5
D	178 ± 2

Derating curve for rated current < 1000 mA









Impedance vs frequency

Z=Impedance, R=Resistance, X=Reactance







Impedance vs frequency, continued

Z=Impedance, R=Resistance, X=Reactance



Impedance vs frequency

Z=Impedance, R=Resistance, X=Reactance



Solder reflow profile




Table 1 - Standard SnPb solder (T_C)

Package thickness	Volume mm ³ <350	Volume mm ³ ≥350
<2.5 mm	235 °C	220 °C
≥2.5 mm	220 °C	220 °C

Table 2 - Lead (Pb) free solder (T_C)

Package thickness	Volume mm ³ <350	Volume mm ³ 350 - 2000	Volume mm ³ >2000
<1.6 mm	260 °C	260 °C	260 °C
1.6 – 2.5 mm	260 °C	250 °C	245 °C
>2.5 mm	250 °C	245 °C	245 °C

Reference J-STD-020

Profile feature	Standard SnPb solder	Lead (Pb) free solder
Preheat and soak		
• Temperature min. (T _{smin})	100 °C	150 °C
• Temperature max. (T _{smax})	150 °C	200 °C
• Time (T _{smin} to T _{smax}) (t _s)	60-120 seconds	60-120 seconds
Ramp up rate T _L to T _P	3 °C/ second max.	3 °C/ second max.
Liquidous temperature (T _L)	183 °C	217 °C
Time (t _L) maintained above T _L	60-150 seconds	60-150 seconds
Peak package body temperature (T _P)*	Table 1	Table 2
Time (t _p)* within 5 °C of the specified classification temperature (T _C)	20 seconds*	30 seconds*
Ramp-down rate (T _P to T _L)	6 °C/ second max.	6 °C/ second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

* Tolerance for peak profile temperature (T_P) is defined as a supplier minimum and a user maximum.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

Eaton
Electronics Division
1000 Eaton Boulevard
Cleveland, OH 44122
United States
Eaton.com/electronics

© 2023 Eaton
All Rights Reserved
Printed in USA
Publication No. ELX1328 BU-ELX22195
March 2023

Eaton is a registered trademark.
All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

