

# LOFPLEAT™ EE economically efficient pleated filter cartridge

Eaton's LOFPLEAT EE all-polypropylene filter cartridges with an economically efficient design are suitable for a wide range of process applications. This disposable filter element can be used for a wide range of applications. The pleated polypropylene filter material provides a large filtration surface area which allows for maximized flow rate in the system.

#### Features and benefits

- Filtration efficiency of 90%
- Retention ratings from 0.2 to 25 μm
- Available in lengths up to 40"
- Pore structure design resists dirt unloading
- Polypropylene construction and multiple gasket/0-ring options for broad application range

#### Design

### Filter material Polypropylene

#### Inner core, cage, end caps Polypropylene

### Gaskets/O-rings

Silicone (standard), Buna-N, EPDM, FPM,

FEP encapsulated (0-rings only)

## Retention ratings 0.2, 0.45, 1, 5, 10, 25 $\mu m$ @ 90% efficiency

#### **Technical data**

# **Nominal lengths** 10", 20", 30", 40" (254, 508, 762, 1016 mm)

### Outside diameter 2.7" (69 mm)

#### Inside diameter 1.1" (27 mm)

### Surface area 5.1 ft<sup>2</sup> (0.47 m<sup>2</sup>) per 10" element

# Max. operating temperature 176 °F (80 °C)

#### Max. differential pressures 58 psid @ 70°F (4.0 bar @ 21°C) 35 psid @ 176°F (2.4 bar @ 80°C)


#### Recommended differential change-out pressure for disposal 29 psid (2.0 bar)



### LOFPLEAT EE economically efficient pleated filter cartridges

#### Flow rate\*

(68°F/20°C per 10" filter cartridge for water)




<sup>\*</sup> For liquids other than water, multiply pressure drop by fluid viscosity in centipoise.



LOFPLEAT EE filter cartridges are available with a variety of gasket, configurations.

### **Ordering code**



- 226/Flat single open end -1:
- -2: 222/Fin single open end
- -3: 226/Fin single open end
- -4: 222/Flat single open end
- Double open end, internal O-ring -10:
- -20: Single open end, internal O-ring
- 222/Fin single open end, triple bayonet

#### North America

44 Apple Street Tinton Falls, NJ 07724 Toll Free: 800 656-3344 (North America only) Tel: +1 732 212-4700

#### Furone/Africa/Middle East Auf der Heide 2

53947 Nettersheim, Germany Tel: +49 2486 809-0

Friedensstraße 41 68804 Altlußheim, Germany Tel: +49 6205 2094-0

An den Nahewiesen 24 55450 Langenlonsheim, Germany Tel: +49 6704 204-0

No. 3, Lane 280, Linhong Road Changning District, 200335 Shanghai, P.R. China Tel: +86 21 5200-0099

100G Pasir Panjang Road #07-08 Singapore 118523 Tel: +65 6825-1668

Bua Clark 2061 - Macuco 13279-400 - Valinhos, Brazil Tel: +55 11 3616-8400

#### For more information, please email us at filtration@eaton.com or visit www.eaton.com/filtration

© 2018 Eaton. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. All information and recommenda-tions appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.

US EF-LPEE 05-2018



-10 μm

-25 μm

**LOFPLEAT EE** 

