

# Reliable, mid-priced filter housing for most applications

Eaton's SIDELINE single bag filter housing is a mid-priced bag filter housing for most industrial applications. This single bag filter housing is a solid, investment-cast filter. Units come standard with filter bag size 01, 02, 03 or 04 stainless steel restrainer baskets.

### **Features**

- Side inlet with evacuation cover prevents spillage of unfiltered liquid, allowing for clean and easy filter bag change-outs
- Cover opening direction easily adapts to different piping layouts and adjusts in the field to accommodate walls, posts or other obstructions

- Compression hold down creates 360 degree sealing between the filter bag and the bag filter housing
- Ergonomic, integral cover handle is easy to open
- Standard design available with threaded or flanged connections
- Smooth, bead-blasted finish, coupled with a minimum twoweld design makes it easy to completely clean the interior
- Designed in accordance with "AD 2000-Merkblätter", EN 13445 and PED

# Options

- Available in 316 Ti stainless steel for high corrosion resistance
- Magnetic inserts to collect metallic chips, fines and dust for sizes 01 and 02
- Buna-N<sup>®</sup> O-rings for the cover are standard. EPDM, Viton<sup>®</sup>, PTFE encapsulated Viton or silicone rubber seals and gaskets are available
- Multiple I/O connections to suit application
- Available with eye-bolt closure or T-bolt closure for faster maintenance

Viton<sup>®</sup> is a registered trademark of E. I. du Pont de Nemours and company.



SIDELINE with T-bolt closure (TSBF)





Compression bag hold down creates 360 degree sealing between filter bag and bag filter housing



Ergonomic, integral cover handle is easy to open and close


# SIDELINE Single Bag Filter Housing

App	lications
-----	-----------

Coarse filtration > 500 $\mu$ m 🖌	
Medium filtration > 10 $\mu$ m $\checkmark$	
Fine filtration < 10 µm	

Pre-filtration	1
Safety filtration	1
High volume	
Batch filtration	1
Circuit filtration	1
Continuous filtration	

Solvents, paints	1			
Fats and oils				
Catalyst, activated carbon				
Acids, bases	1			
Petrochemicals	1			
Water, waste water	1			
Chemical industry	1			
Pharmaceuticals				
Metal cleaning	1			
Automotive				
Electronics				
Food and beverage	1			
Paint and lacquer	1			
Water treatment	1			
Galvanic industry	1			



## **Dimensions - mm**

Model	А	В	С	D	E	G
SBF-0101	220	495	676	365	965	219
SBF-0102	220	890	1070	365	1753	219
SBF-0103	110	300	460	190	584	114
SBF-0104	110	455	616	190	876	114
TSBF-0101	220	495	600	343	825	219
TSBF-0102	220	890	995	343	1220	219
TSBF-0103	110	300	394	220	484	114
TSBF-0104	110	455	550	220	640	114

Dimensions for reference only and approximate. Exact dimensions for installation purposes available on request.

### **Technical data**

Models	No. of filter bags	Size	Flow rate <sup>1</sup> m³/h	Max. pressure bar	Max. temp. °C	Housing volume I	Housing weight kg	l/O connections
SBF-0101	1	1	20	10	160	18	38	DN 50 PN 16 (DIN flange)
SBF-0102	1	2	40	10	160	32	46	DN 50 PN 16 (DIN flange)
SBF-0103	1	3	6	16	160	3	12	1½" BSP female thread
SBF-0104	1	4	12	16	160	4.5	13	1½"BSP female thread
TSBF-0101	1	1	20	6	160	18	38	DN 50 PN 16 (DIN flange)
TSBF-0102	1	2	40	6	160	32	46	DN 50 PN 16 (DIN flange)
TSBF-0103	1	3	6	16	160	3	12	1½" BSP female thread
TSBF-0104	1	4	12	16	160	4.5	13	1½" BSP female thread

<sup>1</sup> Maximum theoretical flow based on water viscosity, filter bag specific.

North America 44 Apple Street Tinton Falls, NJ 07724 Toll Free: 800 656-3344 (North America only) Tel: +1 732 212-4700

Europe/Africa/Middle East Auf der Heide 2 53947 Nettersheim, Germany Tel: +49 2486 809-0

Friedensstraße 41 68804 Altlußheim, Germany Tel: +49 6205 2094-0

An den Nahewiesen 24 55450 Langenlonsheim, Germany Tel: +49 6704 204-0

#### China No. 3, Lane 280, Linhong Road

Linhong Road Changning District, 200335 Shanghai, P.R. China Tel: +86 21 5200-0099

#### Singapore 4 Loyang Lane #04-01/02 Singapore 508914 Tel: +65 6825-1668

Brazil Rua Clark, 2061 - Macuco 13279-400 - Valinhos, Brazil Tel: +55 11 3616-8400

#### For more information, please email us at *filtration@eaton.com* or visit www.eaton.com/filtration

© 2017 Eaton. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. All information and recommendations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations. EN EF-FBH-11 03-2017



