

WPL Spin-On Filters



EATON

Powering Business Worldwide

High performance technology for efficient control of contamination levels in hydraulic, lubrication and engine circuits

Eaton's WPL spin-on filters are designed to provide one of the highest cleanliness levels for hydraulic systems, featuring cartridges that are engineered to fit into many leading filter systems on the market.

These filters are available with the following features:

- Compatible with a variety of mediums such as oils, fuels, emulsions, glycol water and synthetic fluids
- Cartridge pressure value: 10 bar
- Flow rates: up to 180 l/min
- Range of operating temperatures: -10°C to 110°C
- Buna N gaskets
- Connection sizes: 3/4", 1 1/4" and 1 1/2" with BSPP or NPT thread
- Filter sizes: 45, 90, 130, 180 and 260
- Grades of filter fineness: 10P and 10VG

Eaton's WPL spin-on filters are manufactured and tested according to ISO 2941, ISO 3723 and ISO 2942.



Technical data and product selection guide

Spin-on filter series	Nominal sizes	Connection sizes (BSP or NPT thread)	Max. operating pressure (bar)	Filter fineness	Clogging indicator options
WPL	45	¾"	10	10P, 10VG	E-0
	90	1 ¼"			
	130	1 ¼"			
	180	1 ½"			
	260	1 ½"			

Applications

- Cooling circuits
- Lube oil systems
- Power transmissions
- Compressors
- Hydrostatic charge pumps
- Fuel transfer

WPL spin-on filters consist of a head mounted directly in-line with the piping and a cartridge containing a WP filter element. The cartridge seals to the head to prevent leakage. These filters are an effective and economical choice where the line pressure is low, and there are no strong pressure surges. Spin-on filters are easy to replace without special equipment or tooling.

Markets

- Power generation
- Agriculture
- Oil and gas
- Construction
- Forestry
- Mining
- Material handling



North America
18684 Lake Drive East
Chanhassen, MN 55317
Toll Free: +1 800-656-3344
(North America only)
Tel: +1 732-212-4700

Europe/Africa/Middle East
Auf der Heide 2
53947 Nettersheim, Germany
Tel: +49 2486 809-0
Friedensstraße 41
68804 Altlußheim, Germany
Tel: +49 6205 2094-0

An den Nahewiesen 24
55450 Langenlonsheim, Germany
Tel: +49 6704 204-0

Greater China
No. 7, Lane 280,
Linhong Road
Changning District, 200335
Shanghai, P.R. China
Tel: +86 21 2899-3687

Asia-Pacific
100G Pasir Panjang Road
#07-08 Interlocal Centre
Singapore 118523
Tel: +65 6825-1620

**For more information, please
email us at filtration@eaton.com
or visit www.eaton.com/filtration**

© 2024 Eaton. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. All information and recommendations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.

EN
03-2024