CN56135



IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Name and address of the applicant

Name and address of the manufacturer

Name and address of the factory

Note: When more than one factory, please report on page 2

Ratings and principal characteristics

Trademark / Brand (if any)

Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

Additional information (if necessary may also be reported on page 2)

A sample of the product was tested and found to be in conformity with

As shown in the Test Report Ref. No. which forms part of this Certificate

Air Circuit-breakers

Eaton Electrical Inc.

1000 Cherrington Parkway Moon Township, PA 15108, USA

Eaton Electrical Ltd.

No.2 Louyang Road, SIP Suzhou, Jiangsu Province, 215121, P.R.China

Eaton Electrical Ltd.

No.2 Louyang Road, SIP Suzhou, Jiangsu Province, 215121, P.R.China

☑ Additional information on page 2

ctfMode

See the Appendix

Eaton

IZM99N, IZM99H, IN99;

IEC 60947-2:2016/AMD1:2019;IEC 60947-2:2016(5th Edition)

00901-CB2021CQC-100295

This CB Test Certificate is issued by the National Certification Body

CHINA QUALITY CERTIFICATION CENTRE

Section 9, No. 188 Nansihuan Xilu, Beijing 100070 P. R. China Tel: +86-10-83886666 Fax: +86-10-83886282 website: http://www.cqc.com.cn

Date: Ea

Feb.18,2022









CN56135

IZM99N, IZM99H, IN99

Uimp:12kV;

Ui:1000V:

Ue:AC440V,AC690V;

In:4000A,5000A,6300A;

Over-current release: Electronic;

lcs:85kA(IZM99N),100kA(IZM99H);

Icu:85kA(IZM99N),100kA(IZM99H);

Icw:85kA/1s(IZM99N),100kA/1s(IZM99H);

3P,4P;

50/60Hz;

Selectivitycategory:B;

Accessories with electronic circuits:

Shunt Release ST:24VDC,48VDC,110-125VDC/110-127VAC,220-250VDC/208-240VAC, 380VAC;

Undervoltage Release UVR:24VDC,32VDC,48VDC,110-125VDC/110-127VAC, 220-250 VDC/ 208-240VAC,380VAC;

Closing coil: Us: 24VDC,48VDC,110-125VDC/110-127VAC,220-250VDC/208-240VAC

Page 1 of 2

Additional information (if necessary)

Date:

Feb.18,2022

Signature:

Xie ZhaoXu





.01	
AA .	
Type Explanation:	
IZM 99 H 4-V 63 W	
	-W:draw-out version, F:fixed version, CW: draw-out version 220 v configuration, CF: fixed version 220 v configuration Rated current:40-4000A, 50-5000A, 63-6300A Digitrip unit A:standard protection(LI) V:Selectivity protection(LSI) U:Ampere meter(LSI/Current measurement/LCD display) P:Power meter(LSI/Communication/Power andharmonic measurement/LCD display) Blank: No electronic release(only for type IN) Phase poles:3 poles/4 poles Breaking capacity:N-85kA, H-100kA Frame size Circuit breaker
	Page 2 of 2
Additional information (if necessary)	
	谢肇响
Date: Feb.18,2022	Signature: Xie ZhaoXu





CN56135

Name of the factory	Address of the factory
1.Eaton Electrical Group	Santana Industrical Park, Road #2 KM 67.6, Arecibo, PR,
	00612, USA

Additional information (if necessary)

Date: Feb.18,2022

Signature:

