

MLGSUSKIT

Modulay LG Suspension Kit

Assembly Details

- Remove existing screws Qty4 (one each corner) on reverse of panel.
- Affix triangular loop hoops (pointing towards centre of panel, do not exceed 0.5Nm Max torque when re-fixing NB: Threads will be stripped if over torqued i.e. spun past engagement point).
- Assemble swaged wires into ceiling plate.
- Fix ceiling plate to mounting surface using suitable wood screws or appropriate fasteners.
- Connect clutch and clip latches to panel via loop hoops.
- Thread wire into clutch body higher than required and adjust down to required level.
- Ensure suspension fixing tabs do not overlap onto the LED Panel's frame when fixed

MLGSUSKIT

Modulay LG Suspension Kit

Assembly Details

- Remove existing screws Qty4 (one each corner) on reverse of panel.
- Affix triangular loop hoops (pointing towards centre of panel, do not exceed 0.5Nm Max torque when re-fixing NB: Threads will be stripped if over torqued i.e. spun past engagement point).
- Assemble swaged wires into ceiling plate.
- Fix ceiling plate to mounting surface using suitable wood screws or appropriate fasteners.
- Connect clutch and clip latches to panel via loop hoops.
- Thread wire into clutch body higher than required and adjust down to required level.
- Ensure suspension fixing tabs do not overlap onto the LED Panel's frame when fixed