



LED Portable and Stand Worklight

- Maintenance-free LED with 35,000 hours of life
- LED Lumen output equivalent to a 300 watt halogen worklight
- 80% cooler than a 500 watt halogen worklight
- Tripod stand with non-skid feet, adjusts up to 4 feet of total height
- Heavy-duty die cast aluminum housing with durable poly-carbonate lens
- Easy wall mount tab
- Quick disconnect feature for easy release from stand
- 3 foot, 18 gauge, 3-prong grounded power cord (WL2540LP)
- 5 foot, 18 gauge, 3-prong grounded power cord (WL2540LST)
- 5 year warranty



WL2540LP



WL2540LST

Model #	Description	UPC	Unit Carton Dimensions (in.)	Master Carton	Master Carton Dimensions (in.)	Palletization
WL2540LP	2600 Lumen Portable LED Worklight	0 80083 70063 9	7.9W x 10.2H x 7.8D	4 Pk	16.6W x 10.9H x 16.5D	96
WL2540LST	2600 Lumen LED Stand Worklight	0 80083 70806 2	10.6W x 23.1H x 5D	2 Pk	23.7W x 11.3H x 10.8D	36

LED Portable and Stand Worklight

- Maintenance-free LED with 35,000 hours of life
- LED Lumen output equivalent to a 600 watt halogen worklight
- 80% cooler than a 500 watt halogen worklight
- Tripod stand with non-skid feet, adjusts up to 5 feet of total height
- Heavy-duty die cast aluminum housing with durable poly-carbonate lens
- Easy wall mount tab
- Quick disconnect feature for easy release from stand
- 6 foot, 18 gauge, 3-prong grounded power cord
- 5 year warranty



WLT5040LST

Model #	Description	UPC	Unit Carton Dimensions (in.)	Master Carton	Master Carton Dimensions (in.)	Palletization
WLT5040LST	5100 Lumen LED Stand Worklight	0 80083 70808 6	10.7W x 27.5H x 5.1D	2 Pk	28.1W x 11.5H x 11D	32



Powering Business Worldwide

Eaton
1121 Highway 74 South
Peachtree City, GA 30269
P: 770-486-4800
www.eaton.com/lighting

Canada Sales
5925 McLaughlin Road
Mississauga, Ontario L5R 1B8
P: 905-501-3000
F: 905-501-3172

© 2016 Eaton
All Rights Reserved
Printed in USA
Publication No. SA502030EN
January 2016

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Product availability, specifications, and compliances are subject to change without notice.