


COOPER Power Systems
COMPONENTS AND PROTECTIVE EQUIPMENT

TIME-CURRENT CHARACTERISTIC CURVES
MINIMUM MELT
TYPE N-TIN

DRAWN BY JFR [CWD] DATE 11-1-00
REPLACES 02/70 [REV 00] REG. NO. 19892
DWG NO. 42 39642 B | 00

Tests made at 240 Volts ac at HIGH pf at 25°C with no initial load
Standards used as basis for data: ANSI C37.47-1991 (R1992)
MINIMUM TEST POINTS PLOTTED SO VARIATIONS SHOULD BE PLUS
THIS DRAWING WAS PRODUCED ON A CAD SYSTEM, ANY MANUAL REVISION WILL VOID IT.

Reference Data
R240-91-9
Page 1 of 2



COOPER Power Systems
COMPONENTS AND PROTECTIVE EQUIPMENT

TIME-CURRENT CHARACTERISTIC CURVES
MAXIMUM CLEAR
TYPE N-TIN

DRAWN BY JFR [CWD] DATE 11-1-00
REPLACES 02/70 [REV 00] REG. NO. 19892
DWG NO. 42 39642 B | 00

Tests made at RATED Volts ac at LOW pf at 25°C with no initial load
Standards used as basis for data: ANSI C37.47-1991 (R1992)
MINIMUM TEST POINTS PLOTTED SO VARIATIONS SHOULD BE MINUS
THIS DRAWING WAS PRODUCED ON A CAD SYSTEM, ANY MANUAL REVISION WILL VOID IT.

Reference Data
R240-91-9
Page 2 of 2