Certificate of Constancy of Performance

0359-CPR-00426



In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation), this certificate applies to the construction product(s)

Intended use:	Fire Safety
	Digital Lighting (Dongguan) Co. Ltd (DIGLIGCN.01) Xin Min Road, Xin Min District, Changan Town, 523879, Dongguan City, Guangdong Province, China
	and
Produced in the manufacturing plant(s):	Cooper Lighting & Safety Limited (COOPLSUK.01) Wheatley Hall Road, Doncaster, DN2 4NB, United Kingdom
Produced by or for:	Cooper Lighting & Safety Limited Wheatley Hall Road, Doncaster, DN2 4NB, United Kingdom
Product(s):	Addressable Input/Output Units (refer to attached appendix for details and conditions)

Fire Safety

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s):

EN54-17:2005+AC:2007

Fire detection and fire alarm systems – Short-circuit isolators

EN54-18:2005+AC:2007

Fire detection and fire alarm systems - Input/output devices

under system 1 are applied and that the product(s) fulfils all the prescribed requirements set out above.

This certificate was first issued on 14th October 2014 and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly, unless suspended or withdrawn by the product certification body. A review of the product(s) and compliant standard(s) will be carried out after 5 years to ensure continued compliance.

Intertek Testing & Certification Limited Cleeve Road, Leatherhead Surrey, KT22 7SB Tel: + 44 (0)1372 370900 Fax: +44 (0)1372 370977 E-mail: cpd.uk@intertek.com

Notified Body

0359

www.intertek.com

Gordon Ash **Certification Manager**

CM14 5NQ, United Kingdom

Date 01/04/2015 Issue 2

Registered No 3272281 Academy Place, 1-9 Brook Street, Brentwood, Essex,

Re-Issue

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

14/10/2019



Appendix to Certificate of Constancy of Performance 0359-CPR-00426

The details and conditions of use for the Addressable Input/Output Units placed on the market by:

Cooper Lighting & Safety Limited

Wheatley Hall Road, Doncaster, DN2 4NB, United Kingdom

To be used in accordance with the supplier's installation instructions and in conjunction with the following bases, ancillaries, sounder tones and sensitivity settings (*where applicable*):

Products compliant with EN54-17:2005+AC:2007 and EN54-18:2005+AC:2007:

Part Number	Manufacturing Location	Description
COPIO	COOPLSUK.01	Addressable 3 Channel Input / Output Unit with Short-circuit Isolator (Open Protocol)
MCIM-COP	DIGLIGCN.01	Addressable Micro Single Channel Input Unit with Short-circuit Isolator (Open Protocol)
CZMU352-IS	COOPLSUK.01	Addressable Zone Monitor Unit with Short-circuit Isolator (Used with Intrinsically Safe Barrier *)
COPZMU-IS	COOPLSUK.01	Addressable Zone Monitor Unit with Short-circuit Isolator (Open Protocol, used with Intrinsically Safe Barrier *)
COPZMU	COOPLSUK.01	Addressable Zone Monitor Unit with Short-circuit Isolator (Open Protocol)
CIO351S	COOPLSUK.01	Addressable 3 Channel Input / Output Unit with Short-circuit Isolator (Resets on Silence Alarms)
MIO324T	COOPLSUK.01	Addressable 3 Channel Input / Output Unit with Short-circuit Isolator (Triple Address)

* MTL5561 Intrinsically Safe Barrier

Conditions of use:

Suitable for indoor applications

Intertek Testing & Certification Limited, Cleeve Road, Leatherhead, Surrey, KT22 7SB Tel: + 44 (0)1372 370900, Fax: +44 (0)1372 370977, E-mail: cpd.uk@intertek.com

0359-CPR-00426 Issue 2

www.intertek.com

Registered No 3272281 Academy Place, 1-9 Brook Street, Brentwood, Essex, CM14 5NQ, United Kingdom



Appendix to Certificate of Constancy of Performance 0359-CPR-00426 (continued)

Branded Variants

Original Part Number	Alternative Part Number	Branded As	Description
CZMU352-IS	MIU871-IS	Menvier	Addressable Zone Monitor Unit with Short-circuit Isolator (Used with Intrinsically Safe Barrier *)
CIO351S	MIO324S	Menvier	Addressable 3 Channel Input / Output Unit with Short-circuit Isolator (Resets on Silence Alarms)

* MTL5561 Intrinsically Safe Barrier

General Notes:

- 1. Evaluated under Intertek project number 101650853.
- 2. <u>No CE or other type approval is made or inferred outside of the attestation of conformity and the product performance as stipulated on this certificate.</u>

Intertek Testing & Certification Limited, Cleeve Road, Leatherhead, Surrey, KT22 7SB Tel: + 44 (0)1372 370900, Fax: +44 (0)1372 370977, E-mail: <u>cpd.uk@intertek.com</u>

0359-CPR-00426 Issue 2

www.intertek.com

Registered No 3272281 Academy Place, 1-9 Brook Street, Brentwood, Essex, CM14 5NQ, United Kingdom



Appendix to Certificate of Constancy of Performance 0359-CPR-00426 (continued)

Table of	performance fo	or EN54-17:2005+A	AC:2007				
Harmonised technical specification							
Essential characteristics	Performance	Clauses	Notes				
Performance under fire conditions	Pass	5.2	а				
Operational reliability	Pass	4	b, c, d, e, f, g				
Durability of operational reliability; temperature resistance	Pass	5.4, 5.5					
Durability of operational reliability; vibration resistance	Pass	5.9 to 5.12					
Durability of operational reliability; humidity resistance	Pass	5.6, 5.7					
Durability of operational reliability; corrosion resistance	Pass	5.8					
Durability of operational reliability; electrical stability	Pass	5.3, 5.13					
 Applies to Models COPIO, MCIM-COP, C MIO324T. Models COPIO, MCIM-COP, C MIO324T also have a declared performa. a. This is assuming that the effect of th these devices. b. Clause 4.2 is only applicable if the si 	CZMU352-IS, MIU8 nce relating to EN5 e fire is to cause a	371-IS, COPZMU-IS, 54-18:2005+AC:2007. short circuit in the tra	COPZMU, CIO351S, MIO324S ai nsmission path that is protected b	nd			
 b. Clause 4.2 is only applicable if the short-circuit isolator incorporates an integral visual indication of status; an assessment to this clause was therefore not performed. c. Clause 4.3 is only applicable if the short-circuit isolator provides for connections to ancillary devices; an assessment 							
 d. Clause 4.4 is only applicable for detachable short-circuit isolators; an assessment to this clause was therefore not 							
 clause 4.4 is only applicable for detachable short-circuit isolators, an assessment to this clause was therefore not performed. clause 4.5 requires use of a special code or tool, or the breaking or removing of a seal; an assessment to this 							
clause was therefore not performed. f. Clause 4.6 is only applicable if there is provision for on-site adjustment of the short-circuit isolator; an assessment to							
this clause was therefore not performed. g. The manufacturer declared that the short-circuit isolators are not controlled by software; an assessment to Clause 4.9 was therefore not performed.							

Intertek Testing & Certification Limited, Cleeve Road, Leatherhead, Surrey, KT22 7SB Tel: + 44 (0)1372 370900, Fax: +44 (0)1372 370977, E-mail: <u>cpd.uk@intertek.com</u>

0359-CPR-00426 Issue 2

www.intertek.com

Registered No 3272281 Academy Place, 1-9 Brook Street, Brentwood, Essex, CM14 5NQ, United Kingdom



Appendix to Certificate of Constancy of Performance 0359-CPR-00426 (continued)

Table of performance for EN54-18:2005+AC:2007							
Harmonised technical specification							
Essential characteristics	Performance	Clauses	Notes				
Response delay (response time)	-	5.2	а				
Performance under fire conditions	-	5.1.4	b				
Operational reliability	Pass	5.1.4					
Durability of operational reliability temperature resistance	Pass	5.3, 5.4					
Durability of operational reliability; vibration resistance	Pass	5.8 to 5.11					
Durability of operational reliability; humidity resistance	Pass	5.5, 5.6					
Durability of operational reliability; corrosion resistance	Pass	5.7					
Durability of operational reliability; electrical stability	Pass	5.2, 5.12	c				
Notes:		•					

Applies to Models COPIO, MCIM-COP, CZMU352-IS, MIU871-IS, COPZMU-IS, COPZMU, CIO351S, MIO324S and MIO324T. Models COPIO, MCIM-COP, CZMU352-IS, MIU871-IS, COPZMU-IS, COPZMU, CIO351S, MIO324S and MIO324T also have a declared performance relating toEN54-17:2005+AC:2007.

a. Response delays are not a function of the models as detailed above; an assessment was therefore not made.

b. Performance under fire conditions was not assessed as part of this standard.

c. Clauses 5.12a and 5.12b are only applicable for devices that incorporate a mains supply; these clauses were therefore not assessed.

Intertek Testing & Certification Limited, Cleeve Road, Leatherhead, Surrey, KT22 7SB Tel: + 44 (0)1372 370900, Fax: +44 (0)1372 370977, E-mail: <u>cpd.uk@intertek.com</u>

0359-CPR-00426 Issue 2

www.intertek.com

Registered No 3272281 Academy Place, 1-9 Brook Street, Brentwood, Essex, CM14 5NQ, United Kingdom