



Installs in as little
as 15 seconds!

Rapid Ring™ self-adjusting pre-fab ring

Run rings around your competition


Presenting the fastest,
profit-friendly pre-fab solution

Now you can win
tight bids and
beat the profit
squeeze with
our revolutionary
Rapid Ring self-
adjusting ring.

Here's how it works for you:

- Installs in as little as 15 seconds
- Compresses your project schedule
- Yields significant time and cost savings
- Helps increase your profits

Learn more about the ring that will make you more competitive at www.cooperbline.com/RapidRing



Available for 1-Gang, 2-Gang, 3-Gang and 4-Gang SKUs

EATON

Powering Business Worldwide

Rapid Ring™ self-adjusting pre-fab ring

Easy 4-step installation: the ultimate time-saver



1 Remove the protective plate.



2 Connect the wiring device.



3 Position the device assembly.



4 Push the device assembly – and you're done!

Features

- Self-adjusting to various wall thickness and types of tile
- Easy off, quick release protective plate
- Works with wall thickness up to 2"
- Completely tool-free trim-out phase
- Manufactured in the USA with union-made assemblies
- Fits most standard boxes and brackets
- One-source supplier for full line of 1- to 4-gang product offering
- Easy to route around raised surface on the protective plate
- UL Listed for U.S. & Canada

Product Chart

For Use With		Box Plate ¹		Sleeve ^{2, 3}		Sleeve Extender ⁴	
Wiring Device Qty	Electrical Box ⁵	Catalog Number	UPC Number	Catalog Number	UPC Number	Catalog Number	UPC Number
1	4" sq.	B1RRP4C	78205168758	B1RRR	78205168741	B1RRE	78205168745
	4-11/16" sq.	B1RRP5C	78205168760				
2	4" sq.	B2RRP4C ⁸	78205168759	B2RRR	78205168742	B2RRE	78205168746
	4-11/16" sq.	B2RRP5C	78205168761				
3	3-gang ⁶	B3RRPC	78205168762	B3RRR	78205168743	B3RRE	78205168747
4	4-gang ⁷	B4RRPC	78205168763	B4RRR	78205168744	B4RRE	78205168748

1. Protective plate included with box plate.
2. Wall thickness range: ½" minimum to 1-¼" maximum.
3. Stop plates included with sleeve.
4. Sleeve extender is an optional accessory to extend maximum wall thickness range to 2" (order separately, mounting hardware included).

5. Minimum electrical box depth is 2-½".
6. Keyhole knockouts allow use on 2-gang electrical box.
7. Keyhole knockouts allow use on 3-gang electrical box.
8. Not compatible with Iberville™ 4" sq. electrical box.

Support

With a prompt quote response, short lead time and fast jobsite delivery, we provide our customers with the solution they need, when they need it. To learn more about how you can benefit from this revolutionary pre-fab solution, talk to one of our representatives today:

Phone: 800-851-7415
www.cooperblin.com/rapidring

Covered by and/or for use under one or more of the following U.S. patents: 8,575,484 8,658,894

⚠ IMPORTANT

It is **STRONGLY** recommended that the compatibility of all components used be verified by the installer prior to installation through utilization of a mock-up wall using all components to simulate the final installation.

Failure to do so may result in improper or undesirable final installation of the sleeve assembly and require substantial rework of the installation.

The wide range of variables (electrical box type and size, knockout size and location, box mounting bracket, cable and conduit connector size and location, number and size of wires, type and size of wire connectors, finished wall thickness, wiring device type and quantity, etc.) may prevent proper final installation, create insufficient wire space, cause damage to the wall surface and/or support bracket, or cause conductor insulation damage.

Eaton
 1000 Eaton Boulevard
 Cleveland, OH 44122
 United States
Eaton.com

© 2016 Eaton
 All Rights Reserved
 Printed in USA
 Publication No. SA305003EN
 June 2016 CBLRIRR-16

B-Line Division
 509 West Monroe Street
 Highland, IL 62249
 United States
 Phone: 800-851-7415

www.cooperblin.com/rapidring

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

