

## Fuller® 13-Speed Transmissions

RTLO-16913A  
RTLO-18913A  
RTLO-20913A

# RT-13



Versatility and low shift effort in a premium Fuller® transmission. Ideal for many performance-minded fleets including general freight, bulk haulers, doubles/triples, steel haulers, tankers and more.

- RT-13 features patented low-inertia design concept that makes shifting smoother, faster, and easier than ever before.
- Ratio flexibility with 16.9 to 1 overall reduction.
- Gathered gear ratios in hi-range provide potential fuel savings by helping keep RPM's low to remain in the engine's optimum fuel efficiency band.
- Simplified shifting with preselect on all button shifts.
- Faster, smoother range and splitter shifts and improved cold weather performance due to design improvements.
- On selected models an optimized lubrication system provides increased cooling and lubrication for more difficult, harder working applications.
- Quieter operation and increased durability with helical gears in auxiliary section.
- 0.73 and 0.86 overdrives for optimum cruise RPMs.
- Roadranger warranties are available for a wide variety of applications. To find the coverage that applies to your specific vocation, please see the Warranty Guide, at [www.eaton.com/roadranger](http://www.eaton.com/roadranger).



# EATON

Powering Business Worldwide

BACKED BY

## Roadranger

SUPPORT

# Fuller® 13-Speed Transmissions

MODEL	CAPACITY	WEIGHT*	LENGTH**	SPEEDS
RTLO-16913A	1650 lbs.ft. [2237 Nm]	716 lbs. [325 kg]	33.1 in. [841 mm]	13 forward, 2 reverse
RTLO-18913A	1850 lbs.ft. [2508 Nm]	716 lbs. [325 kg]	33.1 in. [841 mm]	13 forward, 2 reverse
RTLO-20913A	2050 lbs.ft. [2779 Nm]	716 lbs. [325 kg]	33.1 in. [841 mm]	13 forward, 2 reverse

\* Less clutch housing, lubricant and end yoke. \*\* Lengths listed are from face of clutch housing to front bottoming surface of companion flange or yoke.

## Specifications:

### Clutch Housing:

- SAE # 1 and # 2. Cast iron and aluminum available.

### PTO Openings:

- Right side, a 45-tooth 6/8 pitch gear. Left side, a 47-tooth 6/8 pitch gear. Both gears turn at .79 of engine speed.

### Oil Capacity:

- Approx. 28 pints [13.25 liters]. Integral oil pump available. Standard on 16913A and 18913A. Oil to water heat exchanger standard on 18913A and 20913A models (Requires 2 pints [.95 liters] additional lubricant).
- Adds 10 lbs. [4.55 kg] to weight).

## Low Inertia Concept:

This innovative, patented design is identified in the Eaton Fuller nomenclature by the letter "L" (as in RTLO-16913A).


These transmissions feature a simple mainshaft which is not splined to the auxiliary gear. This unique design eliminates the added mass, drag and inertia of the entire auxiliary section.

During upshifts, where both the lever and splitter button are moved together, the low-inertia mainshaft is quickly brought to synchronous resulting in fast, easy shifts.


## Ratios and Steps:

GEAR	RATIO	% STEP
8th H	0.73	17
8th L	0.86	17
7th H	1.00	17
7th L	1.17	18
6th H	1.38	17
6th L	1.62	19
5th H	1.94	17
5th L	2.28	17
Range Shift		41
4th	3.23	37
3rd	4.43	38
2nd	6.11	40
1st	8.59	42
Low 1	12.31	
Reverse-HI	3.50	
Reverse-Low	13.22	
Overall Ratio:	16.9 to 1	

## Shift Pattern:



## Performance Chart: RTLO-18913A



Based on 1800 RPM engine operating at 1636 RPM/62 MPH [100 kph].

BACKED BY

**Roadranger**

SUPPORT

For spec'ing or service assistance, call 1-800-826-HELP (4357) or visit [www.eaton.com/roadranger](http://www.eaton.com/roadranger). In Mexico, call 001-800-826-4357.

Roadranger: Eaton and trusted partners providing the best products and services in the industry, ensuring more time on the road.

### Eaton

Vehicle Group  
13100 E. Michigan Ave.  
Galesburg, MI 49053 USA  
800-826-HELP (4357)  
[www.eaton.com/roadranger](http://www.eaton.com/roadranger)

© 2019 Eaton  
All Rights Reserved. Printed in USA.  
TRSL0249 0319

**Note:** Features and specifications listed in this document are subject to change without notice and represent the maximum capabilities of the software and products with all options installed. Although every attempt has been made to ensure the accuracy of information contained within, Eaton makes no representation about the completeness, correctness or accuracy and assumes no responsibility for any errors or omissions. Features and functionality may vary depending on selected options.

Eaton, Fuller, Roadranger, Solo, UltraShift and Fuller Advantage are registered trademarks of Eaton. All trademarks, logos and copyrights are those of their respective owners.